



MASTER TL-D Super 80

MASTER TL-D Super 80 36W/865 1SL/25

The MASTER TL-D Super 80 lamp offers more lumens per watt and better color rendering than TL-D standard colors. Furthermore, it has a lower mercury content. The lamp can be operated in existing TL-D luminaires.

Product data

| General Information | | LLMF 2000 h Rated | |
|------------------------------------|----------------------------------|-------------------------------|-------------|
| Cap-Base | G13 [Medium Bi-Pin Fluorescent] | LLMF 4000 h Rated | 96 % |
| Life To 10% Failures (Nom) | 12000 h | LLMF 6000 h Rated | 95 % |
| Life To 50% Failures (Nom) | 15000 h | LLMF 8000 h Rated | 94 % |
| Life To 50% Failures Preheat (Nom) | 20000 h | LLMF 12000 h Rated | 93 % |
| LSF 2000 h Rated | 99 % | LLMF 16000 h Rated | 92 % |
| LSF 4000 h Rated | 99 % | LLMF 20000 h Rated | 91 % |
| LSF 6000 h Rated | 99 % | | 90 % |
| LSF 8000 h Rated | 99 % | Operating and Electrical | |
| LSF 12000 h Rated | 89 % | Power (Rated) (Nom) | 36.0 W |
| LSF 16000 h Rated | 33 % | Lamp Current (Nom) | 0.440 A |
| LSF 20000 h Rated | 2 % | Temperature | |
| Light Technical | | Design Temperature (Nom) | 25 °C |
| Color Code | 865 [CCT of 6500K] | Controls and Dimming | |
| Luminous Flux (Nom) | 3250 lm | Dimmable | Yes |
| Luminous Flux (Rated) (Nom) | 3250 lm | Mechanical and Housing | |
| Color Designation | Cool Daylight | Cap-Base Information | Green Plate |
| Chromaticity Coordinate X (Nom) | 313 | Approval and Application | |
| Chromaticity Coordinate Y (Nom) | 337 | Energy Efficiency Label (EEL) | A |
| Correlated Color Temperature (Nom) | 6500 K | | |
| Luminous Efficacy (rated) (Nom) | 84 lm/W | | |
| Color Rendering Index (Nom) | 85 | | |

MASTER TL-D Super 80


| | |
|-------------------------------|-------------------------------------|
| Mercury (Hg) Content (Nom) | 2.0 mg |
| Energy Consumption kWh/1000 h | 42 kWh |
| Product Data | |
| Full product code | 871150063207440 |
| Order product name | MASTER TL-D Super 80 36W/865 1SL/25 |
| EAN/UPC - Product | 8711500632074 |
| Order code | 927921086544 |

| | |
|---------------------------------|-------------------|
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 25 |
| Material Nr. (12NC) | 927921086544 |
| Net Weight (Piece) | 135.000 g |
| ILCOS Code | FD-36/65/1B-E-G13 |

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.



Dimensional drawing



| Product | D (max) | A (max) | B (max) | B (min) | C (max) |
|--|---------|-----------|-----------|-----------|-----------|
| MASTER TL-D Super 80 36W/865 1SL/25 | 28 mm | 1199.4 mm | 1206.5 mm | 1204.1 mm | 1213.6 mm |

TL-D 36W/865

Photometric data





Lightcolor /865

Lightcolor /865


MASTER TL-D Super 80

Lifetime



MASTER TL-D Super 80 Life Expectancy 3 h cycle

MASTER TL-D Super 80 Life Expectancy 12 h cycle



MASTER TL-D Super 80 Lumen Maintenance 3 h + 12 h cycle

