



MASTER TL-D Super 80

MASTER TL-D Super 80 15W/840 SLV/25

The MASTER TL-D Super 80 lamp offers more lumens per watt and better color rendering than TL-D standard colors. Furthermore, it has a lower mercury content. The lamp can be operated in existing TL-D luminaires.

Product data

General Information		LLMF 2000 h Rated	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	LLMF 4000 h Rated	96 %
Life To 10% Failures (Nom)	12000 h	LLMF 6000 h Rated	95 %
Life To 50% Failures (Nom)	15000 h	LLMF 8000 h Rated	94 %
Life To 50% Failures Preheat (Nom)	20000 h	LLMF 12000 h Rated	93 %
LSF 2000 h Rated	99 %	LLMF 16000 h Rated	92 %
LSF 4000 h Rated	99 %	LLMF 20000 h Rated	91 %
LSF 6000 h Rated	99 %		90 %
LSF 8000 h Rated	99 %	Operating and Electrical	
LSF 12000 h Rated	89 %	Power (Rated) (Nom)	15.0 W
LSF 16000 h Rated	33 %	Lamp Current (Nom)	0.335 A
LSF 20000 h Rated	2 %	Temperature	
Light Technical		Design Temperature (Nom)	25 °C
Color Code	840 [CCT of 4000K]	Controls and Dimming	
Luminous Flux (Nom)	1000 lm	Dimmable	Yes
Luminous Flux (Rated) (Nom)	1000 lm	Mechanical and Housing	
Color Designation	Cool White (CW)	Cap-Base Information	Green Plate
Chromaticity Coordinate X (Nom)	383	Approval and Application	
Chromaticity Coordinate Y (Nom)	386	Energy Efficiency Label (EEL)	B
Correlated Color Temperature (Nom)	4000 K		
Luminous Efficacy (rated) (Nom)	67 lm/W		
Color Rendering Index (Nom)	82		

MASTER TL-D Super 80


Mercury (Hg) Content (Nom)	2.0 mg
Energy Consumption kWh/1000 h	19 kWh
Product Data	
Full product code	871150070280740
Order product name	MASTER TL-D Super 80 15W/840 SLV/25
EAN/UPC - Product	8711500702807
Order code	927922284014

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	927922284014
Net Weight (Piece)	56.570 g
ILCOS Code	FD-15/40/1B-E-G13

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.



Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL-D Super 80 15W/840 SLV/25	28 mm	437.4 mm	444.5 mm	442.1 mm	451.6 mm

TL-D 15W/840

Photometric data





Lightcolor /840

Lightcolor /840

MASTER TL-D Super 80

Lifetime



MASTER TL-D Super 80 Life Expectancy 3 h cycle

MASTER TL-D Super 80 Life Expectancy 12 h cycle



MASTER TL-D Super 80 Lumen Maintenance 3 h + 12 h cycle

